

Oil Pattern Distance	42	Reverse Brush Drop	36	Oil Per Board	50 uL
Forward Oil Total	18.15 mL	Reverse Oil Total	10.45 mL	Volume Oil Total	28.6 mL
Tank Configuration	A Only	Tank A Conditioner		Tank B Conditioner	

	START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	3	14	3	A	111	0.0	3.9	3.9	5550
2	7L	7R	2	14	3	A	54	3.9	7.8	3.9	2700
3	8L	8R	2	14	3	A	50	7.8	11.7	3.9	2500
4	10L	9R	2	18	3	A	44	11.7	16.8	5.1	2200
5	11L	10R	2	18	3	A	40	16.8	21.9	5.1	2000
6	13L	11R	2	18	3	A	34	21.9	27.0	5.1	1700
7	14L	12R	2	18	3	A	30	27.0	32.1	5.1	1500
8	2L	2R	0	22	3	A	0	32.1	42.0	9.9	0

	START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	30	3	A	0	42.0	30.0	-12.0	0
2	13L	12R	2	22	3	A	32	30.0	23.8	-6.2	1600
3	12L	11R	2	18	3	A	36	23.8	18.7	-5.1	1800
4	9L	9R	2	18	3	A	46	18.7	13.6	-5.1	2300
5	7L	7R	1	18	3	A	27	13.6	11.1	-2.5	1350
6	5L	5R	1	14	3	A	31	11.1	9.2	-1.9	1550
7	2L	2R	1	14	3	A	37	9.2	7.3	-1.9	1850
8	2L	2R	0	14	3	A	0	7.3	0.0	-7.3	0

Cleaner Ratio Main Mix NA Forward
 Cleaner Ratio Back End Mix NA Reverse
 Cleaner Ratio Back End Distance NA Combined
 Buffer RPM: 4 = 700 | 3 = 500 | 2 = 200 | 1 = 100



Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Middle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	4.62	1.71	1.02	1	1.43	4.62

