


Oil Pattern Distance	45	Reverse Brush Drop	40	Oil Per Board	Multi ul
Forward Oil Total	16.38 mL	Reverse Oil Total	18 mL	Volume Oil Total	34.38 mL
Tank Configuration	Multi Tank	Tank A Conditioner	GLIDE	Tank B Conditioner	GLIDE

	START	STOP	LOADS	MICS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	8L	8R	4	45	14	3	A	100	0.0	5.9	5.9	4500
2	2L	2R	6	45	14	3	A	222	5.9	17.8	11.9	9990
3	10L	10R	2	45	14	3	A	42	17.8	21.7	3.9	1890
4	2L	2R	0	45	18	3	A	0	21.7	32.0	10.3	0
5	2L	2R	0	45	22	3	A	0	32.0	40.0	8.0	0
6	2L	2R	0	45	30	1	A	0	40.0	45.0	5.0	0

	START	STOP	LOADS	MICS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	50	30	2	B	0	45.0	34.0	-11.0	0
2	12L	11R	4	50	18	3	B	72	34.0	23.8	-10.2	3600
3	9L	9R	4	50	14	3	B	92	23.8	15.9	-7.9	4600
4	7L	7R	2	50	14	3	B	54	15.9	12.0	-3.9	2700
5	2L	5R	2	50	14	3	B	68	12.0	8.1	-3.9	3400
6	2L	2R	2	50	14	3	B	74	8.1	4.2	-3.9	3700
7	2L	2R	0	50	14	3	B	0	4.2	0.0	-4.2	0

Cleaner Ratio Main Mix 5:1 Forward
 Cleaner Ratio Back End Mix 5:1 Reverse
 Cleaner Ratio Back End Distance 50 Combined
 Buffer RPM: 4 = 650 | 3 = 500 | 2 = 200 | 1 = 100



Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Middle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	2.53	1.24	1	1	1.19	2.76

